IRIS IR-A

Iris is the last short-wave infrared heater designed by MO-EL. It combines its solid Italian manufacturing with low consume and contemporary design.

Iris is protected against dust and rain and can be installed indoor or outdoor as well. It focuses its heat only where it is really necessary.

The versions 866NRC and 867NRC are equipped with remote control for an easier control of the ON/OFF setting. One remote control can activate various appliances, in fact it operates by infrared inputs.

Made to last over time, Iris is made of nylon and aluminum and

can be completely recycled at the end of its life cycle. Easy maintenance: the lamp is replaceable; it is not necessary to completely disassemble the unit. Watch the tutorial on MO-EL's Youtube channel.

3 inclination settings for an easier installation

Iris is extremely light and it is suitable to be installed with the adjustable 1.5 mt retractable arm (models 4467 and 4469). Iris is equipped with wall bracket (coming with the unit) but is also suitable for pole or sun umbrella installation if combined with pole bracket 868p (pole) or 868u (umbrella).

Benefits Accessories IP65 Hanging chains and wall bracket From 1200 W up to 1800 W of power included

Available with remote control (866NRC and 867NRC) With adaptable wall bracket White frozen lamp – quartz and tungsten wire Lamp 5000 h life time

No rust – made in aluminum and nylon PA enhanced with fiber glass Effective indoor and outdoor

Iris is protected against dust and rain, meeting the IP65 standard. It can be installed in any environment. Iris is suitable for wall, pole or parasol positioning. Totally silent

Accessories Hanging chains and wall brackets included Item 868P: Optional Bracket for Pole installation Item 868U: Optional Bracket for Sun umbrella

Dimensions in mm 721x124x83 721x124x83 721x124x83 826x124x83 826x124x83 826x1	24x83
DIITIETISIOTIS ITTITTITTI 721X124X03 721X124X03 721X124X03 020X124X03 020X124X03 020X1	
Weight 0,95 Kg 0,65 Kg 1,05 Kg 1 Kg 0,7 Kg 1,10) Kg
Power Supply 220-240V~50-60Hz 220-2000000000000000000000000000000000	′~50-60Hz
Total Consumption 1200 W 1200 W 1200 W 1800 W	0 W
Cable H05RN-F - H05RN-F - H05R	RN-F
Range of Action 4-6mq 4-6mq 4-6mq 8-10mq 8	0mq
IP Rate IP65 IP65 IP65 IP65 IP65 IP65 IP	65
Insulating Class I I I I I I I	I
Master Box / Pallet q. 4pcs/48 4pcs/48<	s/48
Spectrum of Light IR-A IR-A IR-A IR-A IR-A IR-A IR-A IR-A	I-A
Lamp Life 5000 h 5000 h 5000 h 5000 h 5000 h 5000 h 5000	00 h
Lamp Quartz and tungsten wire Quartz and tungs	ungsten wire
Coming With Switch, Wall bracket Switch , Plug, Wall bracket Switch, Wall bracket Switch , Plug	, Wall bracket
Plug and and Plug and ar	nd
Wall bracketRemote controlWall bracketRemote	e control
Made in ITALY ITALY ITALY ITALY ITALY ITALY ITALY ITA	ALY



